

AMITEK COLOUR

A.P.P. PIGMENT PASTE

- | | |
|------------------|--|
| 1. Appearance | : Viscous Paste |
| 2. Viscosity | : Highly viscous |
| 3. Colour | : As per specified RAL |
| 4. Mixing Ratio | : 8-10% by weight of resin used for SL. |
| 5. Shelf Life | : One year from date of manufacture in original container. |
| 6. Compatibility | : To be mixed with Epoxy Resins part only. |
| 7. Storage | : Keep in cool dry place away from sunlight. |

It is advisable to ascertain suitability of its use and its shade after addition of curing agents or hardners before using mixes for bulk areas to avoid mismatch of colours before and after curing.

DISCLAIMER:

The information above is believed to be accurate & represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use, handling and from contact. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way, AMITEK manufactured by APP Paint Chemicals Private Limited will be liable for any claims, losses, or damages of any third party or for lost any special, indirect, incidental, consequential or exemplary charge, however arising, even APP Paint Chemicals Private Limited has been advised of the possibility of such damages.

MANUFACTURED BY -

APP PAINT CHEMICALS P. LTD.

Call : +91- 9322226360

Email id : sales@apppaintchemicals.com, business@apppaintchemicals.com

Website : www.apppaintchemicals.com